



Representative picture

Technical information

According to IEC 60947-3

Rated thermal current (Ith)	63 A
Rated insulation voltage (Ui)	690 V
Rated impulse withstand voltage (Uimp)	8 kV

AC rated operational current

415 V	AC21A	63 A
415 V	AC22A	63 A
415 V	AC23A	63 A

Rated conditional short-circuit current	15 kA
---	-------

Rated maximum current (gL-gG)	80 A
-------------------------------	------

Rated breaking capacity (400V; cos φ=0,45)	504 A
--	-------

Rated short-time withstand current (1 sec)	1600 A
--	--------

Mechanical durability (according to the standards, for other values please consult)	10000
---	-------

Rigid copper conductor	16/25mm ²
------------------------	----------------------

Flexible copper conductor	10/16 mm ²
---------------------------	-----------------------

Standards



Quality Telergon SAU

ISO 9001 & 14001



According to UL 60947-4-1 - CAN / CSA C22.2 N° 14

Rated thermal current (Ith)	63 A
-----------------------------	------

General use rating	600 Vac
--------------------	---------

AC rated operational power	3x240V	20 HP
----------------------------	--------	-------

Normal service conditions:

Ambient air temperature (°C): -5°...+40°.

Maximum altitude: 2.000 m. Maximum humidity: 90%.


Pollution degree: 3 (standard for industrial applications).

Rated frequency at AC utilization categories: 50/60 Hz.


Rated duties at utilization categories AC21A, AC22A and AC23A:

Continuing (8 hours); uninterrupted.


Diagram, connection & positions



Scheme



Connections




Positions

Visit our website for more information www.telergon.com

Interrupor de levás
T-0005000400E1N1

TELERGON, SAU
Datos sujetos a cambios sin previo
aviso (impreso: 03/07/2024)



Visit our website for more information www.telergon.com

	Interruptor de levass T-0005000400E1N1	TELERGON, SAU Datos sujetos a cambios sin previo aviso (impreso: 03/07/2024)
---	--	---